

## Double acting cylinder



Model	Cylinder capacity	Stroke (mm)	Height (mm)		Oil capacity (cc)	Hydraulic coupling	Pressure (bar)	Weight (kg)
			Retracted	Extended				
TDC-515	5	150	285	435	144	3/8" NPT-18	700	3,1
TDC-530		300	433	733	288			4,4
TDC-1015	10	150	314	464	228			6
TDC-1030		300	464	764	456			8,7
TDC-2515	25	150	363	513	497,7			14
TDC-2530		300	513	813	995,4			19,4
TDC-3015	30	150	398	548	662,6			22,4
TDC-3030		300	548	848	1325,2			30,4
TDC-5015	50	150	343	493	1063			28,5
TDC-5030		300	493	793	2126			39,2
TDC-10015	100	150	352	502	1990			58,6
TDC-10030		300	502	802	3980			82,2
TDC-15015	150	150	381	531	3207			95
TDC-15030		300	531	831	6414			125,6
TDC-20015	200	150	400	550	4253			129
TDC-20030		300	550	850	8506			169
TDC-30015	300	150	433	583	6506			230
TDC-30030		300	583	883	13012			298
TDC-50015	500	150	475	625	10603			490
TDC-50030		300	625	925	21206			590
TDC-80015	800	150	550	700	17462			782
TDC-80030		300	700	1000	34924	989		
TDC-100015	1000	150	610	760	21783	1216		
TDC-100030		300	760	1060	43566	1533		